

OMEGA

Automatic Triple Water Discharge Machine



FEATURES

- Used for water discharge in PVC profiles
- Automatic operation system with pneumatic movement
- 3 high-frequency spindle motors
- Water discharge at different angles and dimensions on 3 different axes
- Upper and lower motors that can be positioned at different angles
- Ability to use motors independently or in pairs
- Button selection of motors according to profile type
- Easy adjustment of the length of the water discharge
- Easy adjustment of motor travel distances according to profile dimensions with a rotary mechanism
- Safe clamp system activated by button

STANDARD EQUIPMENT







- 5 mm Milling bit (3 qty)

OPTIONAL EQUIPMENT

- Conveyor



WEB

| | | | | | | | | | | | | |
|-------------------------------------------------------------------------------------|-----------------|-----------|-------------------|-------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|-----------------|--------------|-----------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  | | | |  | |  | | | |  |  |  |
| HP kw | n | 1 ~ Hz | I (230 V) A | Ø D | Ø d | a | | b | | Air Pressure | Air Consumption | l x w x h (mm) ? kg |
| 0,75 0,55 | 18.000 r.p.m | 50 60 | 3,5 A | 8 mm | 5 mm | min. max. | 40 mm 180 mm | min. max. | 40 mm 160 mm | 6-8 bar | 10 L / min | 935 x 755 x 1600 ? kg |